

Modern, high performance, top-exit printing

Safer. Cleaner. Printers.



Self-protective housing and disinfectant ready

The CT-E301 was not only designed to withstand the harsh chemicals of disinfection products but to stop bacteria in it's tracks too. The technology within the casing and the printer itself has an SIAA mark fulfilling ISO 22196 which further reinforces that it is engineered to deliver effective results against bacteria growth and are designed to the highest industry standards.

Future-proof interface options

The CT-E301 is available in two interface configurations – standard USB or triple interface including USB, Serial and Ethernet. So, no matter what POS system you have in place you'll be able to connect.

Modern, compact design

Designed to have one of the smallest footprints on the market, the CT-E301 is perfect for environments where space is scarce. Easily fit it alongside a cash drawer, integrate it into a kiosk or simply have it displayed on the counter with a scanner.

CT-E301

POS, Receipt printer (thermal 3 inch / 80mm)

Applications

- Hospitality
- Retail
- Healthcare
- Journal
- Kiosk
- Kitchen
- Pharmacy
- Queue Management



More features for reliable printing

CITIZEN

Specifications

| Model | CT-E301 |
|------------------------------|--|
| Printing Technology | Direct Thermal |
| Resolution | 203 dpi |
| Print Speed (maximum) | 250 mm/sec. |
| Print Width (maximum) | 72 mm |
| Media Width (min to max) | 57.5 - 79.5 (+/- 0.5 mm) |
| Roll Size (max), Core Size | 83 mm outside diameter |
| Media Thickness (min to max) | 53 to 85 µm |
| Media Sensor | Paper end |
| Main Interface | Triple interface: Serial, USB and Ethernet |
| Power supply | 100 - 240V, 50/60hz |
| Reliability | 200 Million pulses or 150 Km, 2 million cuts |
| Control panel | 1 button, 2 LEDs |
| Emulations (Languages) | ESC/POS™ |
| Drivers and software | Free-of-charge from website, including support for various platforms |
| Flash (Non-Volatile Memory) | 8MB |
| Size (W x D x H) and Weight | 108 x 125 x 165 mm, 1.3Kg |
| Cutter | Guillotine type, full and partial |
| EMC and safety standards | CE, C-UL, VCCI, FCC class A, UL, CCC |

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CT-E301

POS, Receipt printer (thermal 3 inch / 80mm)

Features & Benefits

- Paper exit: Top exit - ideal for all retail applications
- Paper load: Quick and easy media changing - drop-in paper loading
- Printing Speed: Fast print out of receipts - up to 250mm per seconds
- Low space requirement - integrated power supply enables clean work station
- Mobile-POS ready
- Easy notification - built-in buzzer
- Small footprint
- Tool-free maintenance



Modern, compact and efficient

CITIZEN SYSTEMS EUROPE GMBH